

LG Programmable Logic Controller

*GLOFA* G3F – PIDA  
G4F – PIDA

LG Industrial Systems

# © CONTENTS ©

## Chapter 1. INTRODUCTION

|                    |     |
|--------------------|-----|
| 1.1 Features ..... | 1-1 |
|--------------------|-----|

## Chapter 2. SPECIFICATIONS

|   |      |
|---|------|
| 2.1 General Specifications .....                              | 2-1  |
| 2.2 Performance Specifications .....                          | 2-2  |
| 2.3 Names of Parts and Functions .....                        | 2-3  |
| 2.4 PID Control Action .....                                  | 2-4  |
| 2.4.1 Processing Type .....                                   | 2-4  |
| 1) Velocity Type Processing .....                             | 2-4  |
| 2) Measured Value Derivative Type (Pre-Derivative Type) ..... | 2-4  |
| 2.4.2 Control Actions .....                                   | 2-5  |
| 1) Proportional Action (P Action) .....                       | 2-5  |
| 2) Integral Action (I Action) .....                           | 2-7  |
| 3) Derivative Action (D Action) .....                         | 2-9  |
| 4) PID Action .....   | 2-10 |
| 5) PID Processing Expression .....                            | 2-10 |
| 6) Forward/Reverse Actions .....                              | 2-11 |

## Chapter 3. INSTALLATION

|                                 |     |
|---------------------------------|-----|
| 3.1 Installation Ambience ..... | 3-1 |
| 3.2 Handling Precautions .....  | 3-1 |

## Chapter 4. TROUBLESHOOTING

|            |  |            |
|------------|--|------------|
| <b>4.1</b> | <b>Errors Indicated by RUN LED Flickering</b>      | <b>4-1</b> |
| <b>4.2</b> | <b>Troubleshooting Procedure</b>                   | <b>4-1</b> |
| 4.2.1      | RUN LED Flickering                                 | 4-1        |
| 4.2.2      | RUN LED Off  | 4-1        |
| 4.2.3      | Unreadable Processing Result of PID Control Module | 4-2        |
| 4.2.4      | Run LED of Enabled Loops Off                       | 4-2        |
| 4.2.5      | PID Control Module Hardware Defect                 | 4-2        |

## Chapter 5. DIMENSIONS

|            |                            |            |
|------------|----------------------------|------------|
| <b>5.1</b> | <b>G3F-PIDA Dimensions</b> | <b>5-1</b> |
| <b>5.2</b> | <b>G4F-PIDA Dimensions</b> | <b>5-2</b> |

## Chapter 6. FUNCTION BLOCK

|            |  |            |
|------------|--|------------|
| <b>6.1</b> | <b>Insertion of the Function Blocks for PID Control Module on the GMWIN</b>        | <b>6-1</b> |
| <b>6.2</b> | <b>Function Blocks</b>   | <b>6-2</b> |
| 6.2.1      | Module Initialization (G3F-PIDA:PID5INI, G4F-PIDA:PID3INI)                         | 6-2        |
| 6.2.2      | Manipulated Value(MV) Reading (Array Type) (G3F-PIDA:PID5ARD, G4F-PIDA:PID3ARD)    | 6-3        |
| 6.2.3      | Manipulated Value(MV) Reading (Single Type) (G3F-PIDA : PID5RD, G4F-PIDA : PID3RD) | 6-4        |
| <b>6.3</b> | <b>Errors on Function Block</b>  | <b>6-5</b> |

## Chapter 7. PROGRAMMING

|            |   |             |
|------------|---|-------------|
| <b>7.1</b> | <b>A Program for Controlling an Electric Furnace<br/>(with Applying the A/D Conversion Module, PID Control Module<br/>and D/A Conversion Module)</b>                  | <b>7-1</b>  |
| <b>7.2</b> | <b>A Program for Control Using a RTD (Resistance Temperature Detector)<br/>(with Applying the RTD Input Module, PID Control Module<br/>and D/A Conversion Module)</b> | <b>7-6</b>  |
| <b>7.3</b> | <b>A Program for Control Using a Thermocouple<br/>(with Applying the TC Input Module, PID Control Module and<br/>D/A Conversion Module)</b>                           | <b>7-10</b> |



## SAFETY PRECAUTIONS

Be sure to read carefully the safety precautions given in data sheet and user's manual before operating the module and follow them.

The precautions explained here only apply to the G3F-PIDA and G4F-PIDA.

For safety precautions on the PLC system, see the GLOFA GM3/4 User's Manuals.

A precaution is given with a hazard alert triangular symbol to call your attention, and precautions are represented as follows according to the degree of hazard.

|   |   |   |
|---|---|---|
|  <b>WARNING</b>  | ⇒ | If not provided with proper prevention, it can cause death or fatal injury or considerable loss of property.          |
|  <b>CAUTION</b> | ⇒ | If not properly observed, it can cause a hazard situation to result in severe or slight injury or a loss of property. |

However, a precaution followed with  **CAUTION** can also result in serious conditions.

Both of two symbols indicate that an important content is mentioned, therefore, be sure to observe it.

Keep this manual handy for your quick reference in necessary.

## Installation Precautions



### CAUTION

- ▶ Operate the PLC in the environment conditions given in the general specifications.
- ▶ If operated in other environment not specified in the general specifications, it can cause an electric shock, a fire, malfunction or damage or degradation of the module
- ▶ Make sure the module fixing projections is inserted into the module fixing hole and fixed.
- ▶ Improper installation of the module can cause malfunction, disorder or falling.

## Test Run and Maintenance Precautions



### CAUTION

- ▶ Do not separate the module from the printed circuit board(PCB), or do not remodel the module.  
They can cause disorder, malfunction, damage of the module or a fire.  
When mounting or dismounting the module, perform them after the power has been turned off.
- ▶ Do not perform works while the power is applied, which can cause disorder or malfunction.

## Waste Disposal Precautions



### CAUTION


- ▶ When disposing the module, do it as an industrial waste.

## Chapter 1. INTRODUCTION

These two modules are called G3F-PIDA and G4F-PIDA. The G3F-PIDA is used with the CPU of GLOFA PLC GM1.2.3 series, and the G4F-PIDA is used with the CPU of GM4 series. Hereafter, the two modules will be commonly called the PID control module.

PID control means a control action that in order to keep the object at a value set beforehand (SV), it compares the SV with a sensor-measured value (PV) and when a difference between them is detected the controller makes PV come to be SV by adjusting output to eliminate the difference. The PID control is composed of combinations of Proportional (P), Integral (I) and Derivative (D) actions.

When a difference between SV and PV occurs, proportional, integral, differential quantities are calculated upon that difference and a MV(Manipulated Value) is output.



### 1.1 Features

The features of the PID control module are as follows.

- 1) One module can control various processes separately and at the same time.
- 2) Forward/reverse action selection is available.
- 3) Manually manipulated out (forced to be output by the user), not operation processing output, is available.
- 4) The number of modules available on one base unit is unlimited.

## Chapter 2 . SPECIFICATIONS

### 2.1 General Specifications

Table 2.1 shows the general specifications of GLOFA GM series.

| No | Items                         | Specifications  |                |                                 |                   |  |  | Standard                |
|----|-------------------------------|---|----------------|---------------------------------|-------------------|--|--|-------------------------|
| 1  | Operating ambient temperature | 0 ~ 55℃   |                |                                 |                   |  |  |                         |
| 2  | Storage ambient temperature   | -25 ~ 75℃   |                |                                 |                   |  |  |                         |
| 3  | Operating ambient humidity    | 5 ~ 95%RH, non-condensing   |                |                                 |                   |  |  |                         |
| 4  | Storage ambient humidity      | 5 ~ 95%RH, non-condensing   |                |                                 |                   |  |  |                         |
| 5  | Vibration                     | Occasional vibration  |                |                                 |                   |  |  | IEC 1131-2              |
|    |                               | Frequency   | Acceleration   | Amplitude                       |                   | Sweep count                            |  |                         |
|    |                               | 10≤f<57 Hz  | -              | 0.075 mm                        |                   | 10 times in each direction for X, Y, Z |  |                         |
|    |                               | 57 ≤f≤150 Hz  | 9.8m/s² {1G}   | -                               |                   |  |  |                         |
|    |                               | Continuous vibration  |                |                                 |                   |  |  |                         |
|    |                               | Frequency   | Acceleration   | Amplitude                       |                   |  |  |                         |
|    |                               | 10≤f<57 Hz  | -              | 0.035 mm                        |                   |  |  |                         |
|    |                               | 57≤f≤150 Hz   | 4.9m/s² {0.5G} | -                               |                   |  |  |                         |
| 6  | Shocks                        | *Maximum shock acceleration: 147 m/s² {15G}<br>*Duration time :11 ms<br>*Pulse wave: half sine wave pulse( 3 times in each of X, Y and Z directions ) |                |                                 |                   |  |  | IEC 1131-2              |
| 7  | Noise immunity                | Square wave impulse noise   |                | ± 1,500 V                       |                   |  |  |                         |
|    |                               | Electrostatic discharge   |                | Voltage :4kV(contact discharge) |                   |  |  | IEC 1131-2<br>IEC 801-2 |
|    |                               | Radiated electromagnetic field  |                | 27 ~ 500 MHz, 10 V/m            |                   |  |  | IEC 1131-2<br>IEC 801-3 |
|    |                               | Fast transient burst noise  |                | Severity Level                  | All power modules | Digital I/Os ( Ue ≥ 24 V)              | Digital I/Os (Ue < 24 V)<br>Analog I/Os communication I/Os | IEC 1131-2<br>IEC 801-4 |
|    |                               |   |                | Voltage                         | 2 kV              | 1 kV                                   | 0.25 kV  |                         |
| 8  | Operating atmosphere          | Free from corrosive gases and excessive dust  |                |                                 |                   |  |  |                         |
| 9  | Altitude for use              | Up to 2,000m  |                |                                 |                   |  |  |                         |
| 10 | Pollution degree              | 2 or lower  |                |                                 |                   |  |  |                         |
| 11 | Cooling method                | Self-cooling  |                |                                 |                   |  |  |                         |

[Table 2.1 ] General specifications

#### REMARK

- 1) IEC(International Electrotechnical Commission)  
: The international civilian organization which produces standards for electrical and electronics industry.
- 2) Pollution degree  
: It indicates a standard of operating ambient pollution level.  
The pollution degree 2 means the condition in which normally, only non-conductive pollution occurs.  
Occasionally, however, a temporary conductivity caused by condensation shall be expected.

## 2.2 Performance Specifications

Table. 2.2 shows performance specifications of the PID control module.


| Items  |                           | Specifications   |          |
|--|---------------------------|--|----------|
|  |                           | G3F-PIDA   | G4F-PIDA |
| Setting range of PID constants                       | Proportional constant (P) | 0.01 ~ 100.00<br>( When integral and derivative constants are set to 0.0 sec, proportional action is applied.) |          |
|  | Integral constant (I)     | 0.0 ~ 3000.0 sec<br>( When integral constant is set to 0.0 sec, integral action shall not be applied.)         |          |
|  | Derivative constant (D)   | 0.0 ~ 3000.0 sec<br>( When derivative constant is set to 0.0 sec, derivative action shall not be applied.)     |          |
| Setting range : SV (Set Value)                       |                           | 0 ~ 16,000   |          |
| Input range : PV (Process Value)                     |                           | 0 ~ 16,000   |          |
| Output range : MV (Manipulated Value)                |                           | 0 ~ 16,000   |          |
| Setting range : M_MV<br>(Manually Manipulated Value) |                           | 0 ~ 16,000   |          |
| LED  | RUN / STOP                | RUN : The run LED of corresponding loops ON<br>STOP : The run LED of corresponding loops OFF                   |          |
|  | NORMAL/ERROR              | Normal : RUN LED ON<br>Error : RUN LED flickering  |          |
| Number of PID control loops                          |                           | 32 loops   | 8 loops  |
| Control action                                       |                           | Forward/Reverse action control is available.   |          |
| Control cycle  |                           | 0.1 sec  |          |
| Processing type                                      |                           | Measured value derivative type<br>(Pre-derivative type)  |          |
| Internal current consumption                         |                           | 0.3 A  | 0.2 A    |
| Weight   |                           | 370 g  | 190 g    |

[Table. 2.2 Performance Specifications]



## 2.3 Names of Parts and Functions

The following gives names of parts :



| No. | Descriptions   |
|-----|--|
| ①   | Loop Run LED   |
|     | <p>It shows the PID control module run status.</p> <ul style="list-style-type: none"> <li>● ON : The corresponding loop is running.</li> <li>● OFF : The corresponding loop is running.</li> <li>● Flickering : Error status. Error Value is displayed.</li> </ul> |
| ②   | RUN LED  |
|     | <p>It shows the PID module Operating status.</p> <ul style="list-style-type: none"> <li>● ON: Normal</li> <li>● Flickering : Error</li> </ul>  |

## 2.4 PID Control Action

### 2.4.1 Processing type

#### 1) Velocity type

Velocity type is a processing that in PID processing, the present Manipulated Value(MV) is obtained by adding the calculated variation of MV ( $\Delta MV$ ) to the previous MV

$$MV_n = MV_{n-1} + \Delta MV_n$$

$MV_n$  : Present Manipulated Value  
 $MV_{n-1}$  : Previous Manipulated Value  
 $\Delta MV_n$  : Variation of the Previous Manipulated Value

#### 2) Measured Value Derivative Type (Pre-derivative)

Measured value derivative processing, in PID processing, uses the process value(PV) for the derivative term. Generally, PID processing, when a deviation occurs, operates toward the direction in which the deviation will be reduced.

The deviation occurs due to alteration of set value(SV) or outside disturbances. Therefore, if the deviation is used in the derivative processing, the output of the derivative term changes rapidly when the deviation occur due to alteration of set value (SV). So, to prevent raid changes like that, this processing uses the process value(PV) for the derivative term.

$$MV_n = MV_{n-1} + K_p \times (E_n - E_{n-1}) + K_p \times S / K_i \times E_n + K_p \times K_d / S \times (2PV_n - PV_{n-1} - PV_{n-2})$$

$MV_n$  : Present Manipulated Value  
 $MV_{n-1}$  : Previous Manipulated Value  
 $\Delta MV_n$  : Variation of the Previous Manipulated Value  
 $E_n$  : Present Deviation  
 $E_{n-1}$  : Previous Deviation  
 $K_p$  : Proportional Constant  
 $K_i$  : Integral Constant  
 $K_d$  : Derivative Constant  
 $S$  : Control Cycle (100ms)  
 $PV_n$  : Present Process Quantity (Present Value)  
 $PV_{n-1}$  : One-step previous Process Quantity (Present Value)  
 $PV_{n-2}$  : Two-step previous Process Quantity (Present Value)

## 2.4.2 Control Action


## 1) Proportional Action (P Action)

- (1) P action means a control action that obtains a MV which is proportional to the deviation (E: the difference between SV and PV).
- (2) The expression which denotes the change relationship of E to MV in P action is shown as follows:

$$MV = K_p \times E$$


where  $K_p$  is a proportional constant and means gain.

- (3) When deviation occurs, the MV by P action is shown in Fig. 2.1.




[Fig. 2.1] MV with the proportional action

- (4) As shown in Fig. 2.1, the larger the proportional constant  $K_p$  the larger the MV, that is, the stronger the P action when the deviation(E) is same. Also, the smaller the  $K_p$  the smaller the MV after P action.
- (5) If the  $K_p$  is too large, PV reaches SV swiftly but can make bad effects like oscillations shown in Fig. 2.2 and cause damage in control stability.
- (6) If the  $K_p$  is too small, oscillations do not occur but the velocity with which PV reaches SV slows down and offset can happen as shown in Fig. 2.3.
- (7) Manipulated Value varies within 0 to 16,000.




[Fig. 2.2] When the proportional constant  $K_p$  is large.



[Fig. 2.3] When the proportional constant  $K_p$  is small.

## 2) Integral Action (I Action)

- (1) When a deviation(E) occurs between SV and PV, Integral action continuously adds the deviation to or subtracts it from the MV in accordance time in order to eliminate the deviation  
When a deviation is small it is not expected that the MV will be changed by P action but I action will eliminate it.  
Therefore, the offset which occurs in P action can be eliminated by I action.
- (2) The period of the time from when the deviation has occurred in I action to when the MV of I action become that of P action is called Integration time and represented as  $K_i$ .
- (3) Integral action when a given deviation has occurred is shown as the following Fig. 2.4.



[Fig. 2.4] Integral action at a constant deviation


- (4) Expression of Integral Action is as follows:

$$MV = P \times E + P \times \frac{1}{K_i} \times \int E dt$$


As shown in the expression, Integral action can be made stronger or weaker by adjusting integration time ( $K_i$ ) in I action.

That is, the more the integration time (the longer the integration time) as shown in Fig. 2.5, the lesser the quantity added to or subtracted from the MV and the longer the time needed for the PV to reach the SV. As shown in Fig. 2.6, when the integration time given is short the PV will approach the SV in short time since the quantity added or subtracted become increased. But, If the integration time is too short then oscillations occurs, therefore, the proper P.I value is requested.

- (5) Integral action is used in either PI action in which P action combines with I action or PID action in which P and D actions combine with I action.




[Fig. 2.5] When a long integration time is given.



[Fig. 2.5] When a short integration time is given.

### 3) Derivative Action (D Action)

- (1) When a deviation occurs due to alteration of SV or external disturbances, D action restrains the changes of the deviation by producing MV which is proportioned with the change velocity (a velocity whose deviation changes at every constant interval) in order to eliminate the deviation.
  - ▶ D action gives quick response to control action and has an effect to reduce swiftly the deviation by applying a large control action (in the direction that the deviation will be eliminated) at the earlier time that the deviation occurs.
  - ▶ D action can prevent the large changes of control object due to external conditions.
- (2) The period of time from when the deviation has occurred to when the MV of D action become the MV of P action is called derivative time and represented as  $K_d$ .
- (3) The D action when a given deviation occurred is shown as Fig. 2.7.



[Fig. 2.7] Derivative action at a constant deviation

- (4) The expression of D action is represented as follows:


$$MV = K_p \times E + K_p \times \frac{dE}{dt}$$

- ▶ In this expression, an output proportional with the variation rate of deviation is added to P action quantity.
- ▶ If the derivative time is increased then P action is strengthened.
- ▶ D action is applied when a change of deviation occurs and the deviation at normal state become 0. D action, therefore, do not reduce offset.

- (5) D action is used in either PD action in which P action combines with D action or PID action in which P and I actions combine with D action.

## 4) PID Action

- (1) PID action controls the control object with the manipulation quantity produced by (P+I+D) action.  
 (2) PID action when a given deviation has occurred is shown as the following Fig. 2.8.



[Fig. 2.8] PID action at a constant deviation

## 5) PID Processing Expression


PID expressions are of measured value derivative type.

| Expressions  | Parameters names  |
|--|---|
| $E_n = SV - PV_n$  | <b>MVn</b> : Present Manipulated Value<br><b>MVn-1</b> : One-step-previous Manipulated Value<br><b>En</b> : Present deviation<br><b>En-1</b> : Previous deviation<br><b>Kp</b> : Proportional constant<br><b>Ki</b> : Integral constant<br><b>Kd</b> : Derivative constant<br><b>S</b> : Control cycle (100 ms)<br><b>PVn</b> : Process value<br><b>PVn-1</b> : One-step-previous Process Value<br><b>PVn-2</b> : Two-step-previous Process value |
| $MV_n = MV_{n-1} + K_p \times (E_n - E_{n-1}) + K_p \times S / K_i \times E_n + K_p \times K_d / S \times (2PV_n - PV_{n-1} - PV_{n-2})$ |   |




## 6) Forward/Reverse Actions

- (1) PID control has two kinds of action, forward action and reverse action.
  - a) Forward action makes PV reach SV by outputting MV when PV is less than SV.
  - b) Reverse action makes PV reach SV by outputting MV when PV is more than SV.
- (2) A diagram in which forward and reverse actions are drawn using MV, PV and SV is shown as Fig. 2.9.



[Fig. 2.9] Forward and reverse action with MV, PV and SV

- (3) Fig 2.10 shows examples of process control by forward and reverse actions, respectively.



[Fig. 2.9] Examples of process control by forward and reverse actions

## Chapter 3. INSTALLATION

### 3.1 Installation Ambience

This module has high reliability regardless of its installation ambience. But be sure to check the following for system in higher reliability and stability.

1) Ambience Requirements

Avoid installing this module in locations, which are subjected or exposed to:

- Water leakage and dust a large amount of dust, powder and other conductive power, oil mist, salt, of organic solvent exists.
- Mechanical vibrations of impacts are transmitted directly to the module body.
- Direct sunlight.
- Dew condensation due to sudden temperature change.
- High or low temperatures (outside the range of 0-55 °C)

2) Installing and Wiring

- During wiring or other work, do not allow any wire scraps to enter into the PLC
- Install it on locations that are convenient for operation.
- Make sure that it is not located near high voltage equipment on the same panel.
- Make sure that the distance from the walls of duct and external equipment be 50 mm or more.
- Be sure to be grounded to locations that have good noise immunity.

### 3.2 Handling Precautions

From unpacking to installing the PID control module, be sure to check the following:

- 1) Do not drop it off, and make sure that strong impacts should not be applied.
- 2) Do not dismount printed circuit boards from the case. It can cause malfunctions.
- 3) During wiring, be sure to check any foreign matter like wire scraps should not enter into the upper side of the PLC, and in the event that foreign matter entered into it, always eliminate it.
- 4) Be sure to disconnect electrical power before mounting or dismounting the module.

## Chapter 4. TROUBLESHOOTING

The followings explain errors that could occur during operating the PID control module and their troubleshooting.


### 4.1 Errors Indicated by RUN LED Flickering

Errors indicated by PID control module RUN LED flickering are given below.


| RUN LED Status                 | Error Type          | Loop RUN LED status   |
|--------------------------------|---------------------|-----------------------|
| Flickering<br>(cycle: 0.1 sec) | WDT Error           | Loop "0" RUN LED ON   |
| Flickering<br>(cycle: 0.2 sec) | System Error        | All Loops RUN LED OFF |
|                                | Buffer Memory Error | Loop "1" RUN LED ON   |

### 4.2 Troubleshooting Procedure


#### 4.2.1 RUN LED Flickering




#### 4.2.2 RUN LED Off



#### 4.2.3 Unreadable Processing Result of PID control module



#### 4.2.4 Run LED of enabled Loops Off




#### 4.2.5 PID Control Module Hardware Defect


PID control module hardware defect.  
Contact the nearest agency or service station.

Chapter 5. DIMENSIONS

5.1 G3F-PIDA Dimensions.



5.2 G4F-PIDA Dimensions





## Chapter 6. FUNCTION BLOCKS

The followings explain the function blocks for the PID control module used on the GMWIN  
The types of function block are given here.

| No. | G3F-PIDA | G4F-PIDA | Function                                    |
|-----|----------|----------|---|
| 1   | PID5INI  | PID3NI   | Module Initialization                       |
| 2   | PID5ARD  | PID3ARD  | Reading the Manipulated Value (Array type)  |
| 3   | PID5RD   | PID3RD   | Reading the Manipulated Value (Single type) |

### 6.1 Insertion of the Function Blocks for the PID Control Module on the GMWIN.

Function blocks can be inserted with the following procedures while the GMWIN is running.  
Inserting a function block is only possible when a project is open.



## 6.2 Function Blocks

### 6.2.1 Module Initialization (G3F-PIDA: PID5INI, G4F-PIDA:PID3INI)

Module initialization function block specifies PID control module base location, slot location, run loop enable/disable and forward/reverse action, and sets MV, M\_MV and P.I.D constants for use in program.

| Function Block        | I/O        | Variable | Data Type                  | Descriptions  |
|-----------------------|------------|----------|----------------------------|---|
| <b>G3F – PIDA</b><br> | In<br>Put  | REQ      | BOOL                       | Function block execution request area<br>- Used to request an execution of the initialization function block<br>- If the conditions connected with this area are established while program is running and "0" changes into "1", the initialization function block is executed |
|                       |            | BASE     | USINT                      | Base location No.<br>- Used to write the base No. where the PID control module is mounted.<br>- Setting range: GM1 series(0~31), GM2 series(0~7), GM3/4 series(0-3)   |
|                       |            | SLOT     | USINT                      | Slot location No.<br>- Used to write slot No. where the PID control module is mounted.<br>- Setting range: 0~7  |
|                       |            | LOOP     | BOOL<br>[Array]<br>*Note 1 | Run loop enable/disable specification<br>- Used to enable or disable a loop for run.<br>- Specify "1" for enabling, and "0" for disabling   |
|                       |            | D/R      | BOOL<br>[Array]<br>*Note 1 | Forward/Reverse action specification for a run loop.<br>- Specify "0" for forward action and "1" for reverse action.  |
|                       |            | SV       | BOOL<br>[Array]<br>*Note 1 | Setting a SV for a run loop<br>- Setting range: 0~16000   |
|                       |            | M_MV     | INT<br>[Array]<br>*Note 1  | Setting a M_MV for a run loop<br>- Setting range: 0 ~ 16000   |
|                       |            | P        | UINT<br>[Array]<br>*Note 1 | Setting a proportional constant (0.01 ~ 100.00) for a run loop<br>- Setting range: 0~10000<br>- The initialization function block not executed if the proportional constant is set to "0", whether or not the constant is initialized in the function block.                  |
|                       |            | I        | UINT<br>[Array]<br>*Note 1 | Setting an integral constant (0.0 ~ 3000.0 sec) for a run loop<br>- Setting range: 0~30000<br>- Integral action not executed if the integral constant is set to '0'.  |
|                       |            | D        | UINT<br>[Array]<br>*Note 1 | Setting a derivative constant (0.0 ~ 3000.0 sec) for a run loop<br>- Setting range: 0~30000<br>- Derivative action not executed if the derivative constant is set to '0'.   |
| <b>G4F – PIDA</b><br> | Out<br>Put | DONE     | BOOL                       | Function block finished execution status<br>- "1" is output when the initialization function block is finished with no error and "1" remains until next execution. If an error occur, '0' is displayed and the operation enters into the stop state.                          |
|                       |            | STAT     | USINT                      | Error status indication area<br>- Used to output the number of an error when it occurs during initialization function block execution.<br>- For description of errors, see GM Section 6.3   |
|                       |            | ACT      | BOOL<br>[Array]<br>*Note 1 | Run loop status indication area<br>- After the initialization function block is finished with no error, "1" is output if the loop is in normal state. But "0" is output for the disabled loops.   |



#### REMARK

\* Note 1: The numbers of Array are 32 in G3F-PIDA, 8 in G4F-PIDA.



## 6.2.2 Manipulated Value(MV) Reading (Array type) : (G3F-PIDA:PID5ARD, G4F-PIDA:PID3ARD)

The Array type MV Reading function block execute all loops of the PID control module in a batch processing and can display the MV for run loops which is output with auto/manual run specification and a PV input.



| Function Block   | I/O | Variable | Data Type                  | Descriptions   |
|--|-----|----------|----------------------------|--|
| <b>G3F – PIDA</b><br>   | I   | REQ      | BOOL                       | Function block execution request area<br>- Used to request an execution of the MV reading function block<br>- If the conditions connected with this area are established while program is running and "0" changes into "1", the MV reading function block is executed. |
|  |     | BASE     | USINT                      | Base location No.<br>- Used to write the base No. where the PID control module is mounted.<br>- Setting range: GM1 series(0~31), GM2 series(0~7), GM3/4 series(0-3)  |
|  |     | SLOT     | USINT                      | Slot location No.<br>- Used to write slot No. where the PID control module is mounted.<br>- Setting range: 0~7   |
|  |     | LOOP     | BOOL<br>[Array]<br>*Note 1 | Run loop enable/disable specification<br>- Used to enable or disable a loop for run.<br>- Specify "1" for enabling, and "0" for disabling  |
|  |     | PV       | INT<br>[Array]<br>*Note 1  | Inputting a PV of the control object for a run loop<br>- Setting range: 0~16000  |
|  |     | A/M      | BOOL<br>[Array]<br>*Note 1 | MV type specification for a run loop<br>- Specify "0" for auto processing (PID processing) MV<br>- Specify "1" for manual processing (forced processing) MV  |
|  |     |          |                            |  |
| <b>G4F – PIDA</b><br> | O   | DONE     | BOOL                       | Function block finished execution status<br>- "1" is output when the initialization function block is finished with no error and "1" remains until next execution. If an error occur, '0' is displayed and the operation enters into the stop state.                   |
|  |     | STAT     | USINT                      | Error status indication area<br>- Used to output the number of an error when it occurs during initialization function block execution.<br>- For description of errors, see GM Section 6.3  |
|  |     | ACT      | BOOL<br>[Array]<br>*Note 1 | Run loop status indication area<br>- After the initialization function block is finished with no error, "1" is output if the loop is in normal state. But "0" is output for the disabled loops.  |
|  |     | MV       | INT<br>[Array]<br>*Note 1  | MV data for the enabled run loops<br>- MV output range: 0 ~ 16000  |

**REMARK**

\*Note 1: The numbers of Array are 32 in G3F-PIDA, 8 in G4F-PIDA.

### 6.2.3 Manipulated Value(MV) Reading (Single type) : (G3F-PIDA:PID5RD, G4F-PIDA:PID3RD)

The single type MV Reading function block processes one loop of the PID control module and can display the MV for run loops which is output with auto/manual run specification and a PV input.

| Function Block   | I/O | Variable | Data Type | Description  |
|--|-----|----------|-----------|--|
| <b>G3F – PIDA</b><br>   | I   | REQ      | BOOL      | Function block execution request area<br>- Used to request an execution of the MV reading function block<br>- If the conditions connected with this area are established while program is running and "0" changes into "1", the MV reading function block is executed. |
|  |     | BASE     | USINT     | Base location No.<br>- Used to write the base No. where the PID control module is mounted.<br>- Setting range: GM1 series(0~31), GM2 series(0~7), GM3/4 series(0~3)  |
|  |     | SLOT     | USINT     | Slot location No.<br>- Used to write the slot No. where the PID control module is mounted.<br>- Setting range: 0~7   |
|  |     | LOOP     | USINT     | Specifying the loop that will read MV<br>- Setting range : G3F-PIDA: 0 to 31, G4F-PIDA: 0 to 7   |
|  |     | PV       | INT       | Inputting a PV of the control object for a run loop<br>- Setting range: 0~16000  |
|  |     | A/M      | BOOL      | MV type specification for a run loop<br>- Specify "0" for auto processing (PID processing) MV<br>- Specify "1" for manual processing (forced processing) MV  |
|  |     |          |           |  |
| <b>G4F – PIDA</b><br> | O   | DONE     | BOOL      | Function block finished execution status<br>- "1" is output when the initialization function block is finished with no error and "1" remains until next execution. If an error occur, '0' is displayed and the operation enters into the stop state.                   |
|  |     | STAT     | USINT     | Error status indication area<br>- Used to output the number of an error when it occurs during initialization function block execution.<br>- For description of errors, see GM Section 6.3  |
|  |     | MV       | INT       | MV data for the enabled run loops<br>- MV output range: 0 ~ 16000  |

### 6.3 Errors on Function Block


Errors indicated by an output variable STAT and their corrective actions are explained.

| STAT No. | Item  | Descriptions   | Function Block      |         |        | Corrective Action   |
|----------|-------|--|---------------------|---------|--------|---|
|          |       |  | Initilaiza-<br>tion | Reading |        |   |
|          |       |  |                     | Array   | Single |   |
| 0        | Local | Normal Run status  | O                   | O       | O      | —   |
| 1        |       | Base location No. outside the setting range                          | O                   | O       | O      | Adjust it within the setting range (See Section GM 6.2)   |
| 2        |       | The corresponding base unit hardware defect                          | O                   | O       | O      | Contact a service station   |
| 3        |       | Slot location No. outside the setting range                          | O                   | O       | O      | Specify correctly the slot No. where the PID control module is mounted .  |
| 4        |       | The specified slot has no PID control module                         | O                   | O       | O      | Mount the PID control module on the specified slot.   |
| 5        |       | A module other than the PID control module is loaded on.             | O                   | O       | O      | Mount the PID control module on the specified slot.   |
| 6        |       | Loop No. outside the setting range                                   | —                   | —       | O      | Specify correctly the No. of the run loop.  |
| 7        |       | PID control Module hardware Defect                                   | O                   | O       | O      | Contact a service station.  |
| 8        |       | PID control module shared memory defect                              | O                   | O       | O      | Contact a service station.  |
| 9        |       | The run loop was not specified in the Initialization function block. | —                   | O       | O      | Specify correctly run loops in the initialization function block.   |
| 10       |       | Inputs outside the setting range                                     | O                   | O       | O      | One or more of SV, M_MV, P, I, D and PV outside the setting range, adjust it/them within its/their setting range. |

## Chapter 7. PROGRAMMING

### 7.1 A Program for Controlling an Electric Furnace (with Applying the A/D Conversion Module, PID Control Module and D/A Conversion Module)

#### 1) System Configuration



#### 2) Initial Settings


- (1) PID control module
  - A) Used loop : loop 0
  - B) Specifying forward/reverse action : forward action
  - C) Setting SV: 12800
  - D) Specifying auto/manual processing : auto processing
- (2) A/D conversion module
  - A) Used channel: channel 0
  - B) Specifying output data type: -192 to 16191
  - C) Setting filter constant: 50
- (3) D/A conversion module
  - A) Used channel: channel 0
  - B) Specifying input data type: -192 to 16191
  - C) The output when no channel is used or the CPU module is in the stop state : The median value of the output will be output.

#### 3) Descriptions of the Program


- (1) A temperature 0 to 200°C from the temperature sensor is converted into an analog signal 4 to 20 mA and then the signal is input to the channel 0 of the A/D conversion module channel and converted into a digital value 9600 to 16000.

- (2) In the PID control module, 100°C (where the signal converter output is 12 mA and 12800 as a digital value.) is set as SV. With regards to P.I.D constants, the manipulated value in the BCD digital switch is set to the proportional constant when %I0.1.0 is on, to the integral constant when %I0.1.1 is on, and to the derivative constant when %I0.1.2 is on.
- (3) MV, the result from PID processing is output at the channel 0 of the D/A conversion module.
- (4) If %I0.1.3 turns on, initial setting of the A/D conversion module, PID control module and D/A conversion module is executed.

#### 1) Modules and their Signal Processing



5) Program






## 6) I/O Variables Used in the Program

| Variable Name | Var_Kind | Data Type                | (AT Address) | (Initial Value)   |
|---------------|----------|--------------------------|--------------|---|
| AD_ACTO       | : VAR    | : ARRAY [0..15] OF BOOL  |              |   |
| AD_CH         | : VAR    | : ARRAY [0..15] OF BOOL  | : = {        | 1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }                                       |
| AD_DATA       | : VAR    | : INT                    |              |   |
| AD_INI        | : VAR    | : FB Instance            |              |   |
| AD_RD         | : VAR    | : FB Instance            |              |   |
| AD_STAT0      | : VAR    | : USINT                  |              |   |
| AD_STAT1      | : VAR    | : USINT                  |              |   |
| AVG_EN        | : VAR    | : ARRAY [0..3] OF BOOL   | : = {        | 0.0.0.0 }   |
| AVG_SEL       | : VAR    | : ARRAY [0..3] OF BOOL   | : = {        | 0.0.0.0 }   |
| D_DATA        | : VAR    | : ARRAY [0..31] OF UINT  | : = {        | 0.0 }       |
| D_R           | : VAR    | : ARRAY [0..31] OF BOOL  | : = {        | 0.0 }       |
| DA_ACTO       | : VAR    | : ARRAY [0..15] OF BOOL  |              |   |
| DA_CH         | : VAR    | : ARRAY [0..15] OF BOOL  | : = {        | 1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }                                   |
| DA_DATA       | : VAR    | : INT                    |              |   |
| DA_INI        | : VAR    | : FB Instance            |              |   |
| DA_STAT0      | : VAR    | : USINT                  |              |   |
| DA_STAT1      | : VAR    | : USINT                  |              |   |
| DA_WR         | : VAR    | : FB Instance            |              |   |
| DATATYPE      | : VAR    | : ARRAY [0..15] OF BOOL  | : = {        | 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }                                   |
| FILT_EN       | : VAR    | : ARRAY [0..3] OF BOOL   | : = {        | 1.0.0.0 }   |
| FILT_VAL      | : VAR    | : ARRAY [0..3] OF USINT  | : = {        | 50.0.0.0 }  |
| I_DATA        | : VAR    | : ARRAY [0..31] OF UINT  | : = {        | 0.0 }       |
| INPUT         | : VAR    | : DINT                   |              |   |
| M_MV          | : VAR    | : ARRAY [0..31] OF INT   | : = {        | 0.0 }       |
| NUM_TIME      | : VAR    | : ARRAY [0..3] OF UINT   | : = {        | 0.0.0.0 }   |
| OUTPUT        | : VAR    | : UINT                   |              |   |
| P_DATA        | : VAR    | : ARRAY [0..31] OF UINT  | : = {        | 1.0 }       |
| PID_ACTO      | : VAR    | : ARRAY [0..31] OF BOOL  |              |   |
| PID_INI       | : VAR    | : FB Instance            |              |   |
| PID_LOOP      | : VAR    | : ARRAY [0..31] OF BOOL  | : = {        | 1.0 }       |
| PID_RD        | : VAR    | : FB Instance            |              |   |
| PID_STAT0     | : VAR    | : USINT                  |              |   |
| PID_STAT1     | : VAR    | : USINT                  |              |   |
| SELECT        | : VAR    | : ARRAY [0..15] OF USINT | : = {        | 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }                                   |
| SV            | : VAR    | : ARRAY [0..31] OF INT   | : = {        | 12800.0 } |



## 7.2 A Program for Control Using a RTD (with Applying the RTD Input Module, PID Control Module and D/A Conversion Module)

### 1) System Configuration




### 2) Initial Settings

- (1) PID control module
  - A) Specifying used loop : loop 0
  - B) Specifying forward/reverse action: forward action
  - C) Specifying auto/manual processing : auto processing
- (2) RTD input module
  - A) Specifying used channel: channel 0
  - B) Specifying RTD sensor type: Pt100
- (3) D/A conversion module
  - A) Setting the voltage input range to -5 to 5 VDC (offset: 1 VDC, gain: 3 VDC)
  - B) Specifying used channel : channel 0
  - C) Specifying input data type : 0 to 16000

### 3) Descriptions of the Program

- (1) The channel 0 of the RTD input module detects a temperature of the electric furnace through Pt100 and receives it as a digital value.
- (2) The Set Value of PID control module loop 0 is set to 8000(where the temperature is 100C). With regards to P.I.D constants, the manipulated value in the BCD digital switch is set to the proportional constant when %IO.1.2 is turned on, as the integral constant when %IO.1.3 is turned on, and as the derivative constant when %IO.1.4 is turned on.
- (3) As the change of MV, the manipulated value in the BCD digital switch is set to a new MV when %IO.1.0 is turned on.
- (4) MV, the result from PID processing is output at the channel 0 of the D/A conversion module.
- (5) If %IO.1.1 turns on, PV is displayed on the BCD digital display.

4) Program








### 7.3 A Program for Control Using a Thermocouple (with Applying the TC Input module, PID Control Module and D/A Conversion Module)

#### 1) System Configuration




#### 2) Initial Settings


- (1) TC input module
  - A) Specifying used channel : channel 0
  - B) Specifying TC type: K type
- (2) PID control module
  - A) Specifying used loop : loop 0
  - B) Specifying forward/reverse action: forward action
  - C) Specifying auto/manual processing : auto processing
  - D) Setting SV: 200°C (4571 as digital value)
  - E) Setting M\_MV (Used when errors occur) : 4500
  - F) Setting P : 3000
  - G) Setting I : 100
  - H) Setting D : 100
  - I) Auto processing is changed to manual processing when errors occur.
- (3) D/A conversion module
  - A) Specifying used channel: channel 0
  - B) Specifying input data type: -192 to 16191
  - C) Output when the CPU module is in the stop state : The median value of the output range is output.

#### 3) Descriptions of the Program

- 1) The temperature of the electric furnace is converted into a digital value through the channel 0 of the thermocouple input module, and the digital value in the reading function block output variable SCAL is used as PV of the PID control module.
- 2) The MV of the PID control module is used as input digital data of the channel 0 of the D/A conversion module.
- 3) If ALM, an output variable of the reading function block of the thermocouple input module turns On, A/M, an input variable of the read function block of the PID control module changes from "0" to "1" and the manual control processing is executed.

## 4) Program





### 5) I/O Variables Used in the Program

| Variable Name | Var_Kind | Data Type                | (AT Address) | (Initial Value)   |
|---------------|----------|--------------------------|--------------|---|
| AUTO          | : VAR    | : BOOL                   |              |   |
| CHO_TEMP      | : VAR    | : INT                    |              |   |
| D             | : VAR    | : ARRAY [0..31] OF UINT  | = {          | { 100.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 } |
| DA_ACTO       | : VAR    | : ARRAY [0..15] OF BOOL  |              |   |
| DA_CH         | : VAR    | : ARRAY [0..15] OF BOOL  | = {          | { 1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| DA_CHO_OUTPUT | : VAR    | : INT                    |              |   |
| DA_INI        | : VAR    | : FB Instance            |              |   |
| DA_INITIAL    | : VAR    | : BOOL                   |              |   |
| DA_STATO      | : VAR    | : USINT                  |              |   |
| DA_STAT1      | : VAR    | : USINT                  |              |   |
| DA_WR         | : VAR    | : FB Instance            |              |   |
| DIRECT        | : VAR    | : ARRAY [0..31] OF BOOL  | = {          | { 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }      |
| I             | : VAR    | : ARRAY [0..31] OF UINT  | = {          | { 100.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }    |
| K_TYPE        | : VAR    | : ARRAY [0..15] OF USINT | = {          | { 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| MANUAL        | : VAR    | : ARRAY [0..31] OF INT   | = {          | { 4500.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| P             | : VAR    | : ARRAY [0..31] OF UINT  | = {          | { 3000.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| PID_ACTO      | : VAR    | : ARRAY [0..31] OF BOOL  |              |   |
| PID_INI       | : VAR    | : FB Instance            |              |   |
| PID_INITIAL   | : VAR    | : BOOL                   |              |   |
| PID_LOOP      | : VAR    | : ARRAY [0..31] OF BOOL  | = {          | { 1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }      |
| PID_RD        | : VAR    | : FB Instance            |              |   |
| PID_READY     | : VAR    | : BOOL                   |              |   |
| PID_STATO     | : VAR    | : USINT                  |              |   |
| PID_STAT1     | : VAR    | : USINT                  |              |   |
| SELECT        | : VAR    | : ARRAY [0..15] OF USINT | = {          | { 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| SET_VALU      | : VAR    | : ARRAY [0..31] OF INT   | = {          | { 4571.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0<br>0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| TC_ACTO       | : VAR    | : ARRAY [0..15] OF BOOL  |              |   |
| TC_ALARM      | : VAR    | : BOOL                   |              |   |
| TC_CH         | : VAR    | : ARRAY [0..15] OF BOOL  | = {          | { 1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |
| TC_CHO_INPUT  | : VAR    | : INT                    |              |   |
| TC_ERROR      | : VAR    | : BOOL                   |              |   |
| TC_INI        | : VAR    | : FB Instance            |              |   |
| TC_INITIAL    | : VAR    | : BOOL                   |              |   |
| TC_RD         | : VAR    | : FB Instance            |              |   |
| TC_READY      | : VAR    | : BOOL                   |              |   |
| TC_STATO      | : VAR    | : USINT                  |              |   |
| TC_STAT1      | : VAR    | : USINT                  |              |   |
| TYPE_0        | : VAR    | : ARRAY [0..15] OF BOOL  | = {          | { 0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0 }   |